



This RFID Vehicle Hang tag is an ideal solution when only temporary access control is required as the hang tag is removable and reusable.

The RFID Vehicle Hang Tag for review mirror is an optimal choice for access control for parking, in gated communities or anywhere vehicles access is required. It is an ideal solution when only temporary access control is required as the hang tag is removable and reusable and do not require permanent attachment to the windshield. The hang tag has a read range of over 5 meters (18 feet). The tag is encapsulated in rigid polyester and may be subsurface printed with a logo and bar code and other information or designs.

Application

- ✓ Vehicle Tracking
- ✓ Car Washes
- ✓ Fleet Management
- ✓ Gated Community - Controlled Access

Technical Specifications

Operating Frequency	860 MHz to 960 MHz
Sizes	3 1/2" x 3 1/2" 3 1/2" x 6 1/2"
Read Range	5+ m; 18+ feet
Construction	Specialized RFID inlay encapsulated between .003" laminated thick polyester laminated to .010" thick polyester; approximately .026" total product thickness
Operating Temperature	-25 °C to 79 °C; -13 °F to 175 °F
RF Protocol	ISO/IEC 18000-6C EPC Class 1 Gen 2
RoHS	2002/95/EC Compliant



GAO RFID Inc.

A Member of GAO Group

Celebrating Over 15 Year of Innovation

Product Overview

RFID Vehicle Hang Tag

116052



GAO Group

GAORFID.com

GAOTek.com

GAORFIDAssetTracking.com

GAOComm.com

GAOInstruments.com

GAOFiberOptics.com

GAOEmbedded.com

GAOResearch.com

Toll Free (USA & Canada)

1-877-585-9555

All Other Areas

416-292-0038

Dial Ext.601 for Sales
Ext.602 for Other Inquiries

sales@GAORFID.com